

# H174-A80-IAS1

High Density Server - 1U 2-Node DP 4-Bay Gen5 NVMe/SATA/SAS-4 Immersion



## Key Features

- Immersion Cooling Server
- 1U 2-node server system
- Dual Intel® Xeon® 6900-Series Processors per node
- 12-Channel DDR5 RDIMM / MRDIMM, 24 x DIMMs per node
- Dual ROM Architecture
- 4 x 1Gb/s LAN ports via Intel® I350-AM2
- 4 x 2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 4 x LP PCIe Gen5 x16 slots
- 1+1 3200W 80 PLUS Titanium redundant power supplies

## Applications

High-Performance Computing Server, High Converged Server, Servers for Hybrid/Private Cloud...

## Specification

Dimensions	1U 2-Node (W440 x H43.4 x D855 mm)	RAID	Require RAID add-in cards Onboard VROC key header
Motherboard	MA84-HD0	PCIe Expansion Slots	4 x LP PCIe Gen5 x16
CPU	Intel® Xeon® 6 Processors - Intel® Xeon® 6900-Series Processors Dual processor per node, TDP up to 500W	I/O Ports	<b>Top:</b> 4 x USB 3.2 Gen1, 2 x Mini-DP, 4 x RJ45, 2 x MLAN
OS Compatibility	<a href="#">OS Support List</a>	Backplane Board	PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s
Socket	4 x LGA 7529 (Socket BR)	TPM	2 x TPM headers (SPI), Optional TPM2.0 kit: CTM012 2 x PRoT connectors (only enabled on RoT SKU)
Chipset	System on Chip	Power Supply	1+1 3200W 80 PLUS Titanium redundant power supplies AC Input: 100-240V  *The system power supply requires C19 power cord.
Memory	12-Channel DDR5 RDIMM/MRDIMM, 48 x DIMMs [RDIMM] Up to 6400 MT/s [MRDIMM] Up to 8800 MT/s <sup>[1]</sup>	System Management	ASPEED® AST2600 Baseboard Management Controller ASPEED® AST2620 Chassis Management Controller GIGABYTE Management Console web interface
LAN	4 x 1Gb/s LAN (2 x Intel® I350-AM2), Support NCSI 2 x 10/100/1000 Mbps Management LAN	Operating Properties	Operating coolant temperature: 20°C to 35°C Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Video	Integrated in ASPEED® AST2600 x 2 - 2 x Mini-DP	Packaging Content	1 x H174-A80-IAS1 4 x CPU heatsinks 1 x Mini-DP to D-Sub cable 4 x Carriers
Storage	<b>Bottom hot-swap:</b> 4 x 2.5" Gen5 NVMe/SATA/SAS-4 <sup>[1]</sup>  [1] Storage card is required to support SATA and SAS drives.	Ordering Part Numbers	6NH174A80DR000IAS1*



Learn more at: <https://www.gigabyte.com/Enterprise>

\* All specifications are subject to change without notice. Please visit our website for the latest information.

\* All trademarks and logos are the properties of their respective holders.

© 2025 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

