


H374-A81-IAW1

High Density Server - 3U 4-Node DP 8-Bay Gen5 NVMe/SATA/SAS-4 Immersion



Key Features

- Immersion Cooling Server
- 3U 4-node server system
- Dual Intel® Xeon® 6900-Series Processors per node
- 12-Channel DDR5 RDIMM / MRDIMM, 24 x DIMMs per node
- Dual ROM Architecture
- 8 x 1Gb/s LAN ports via Intel® I350-AM2
- 8 x 2.5" Gen5 NVMe/SATA/SAS-4 bays
- 16 x LP PCIe Gen5 x16 slots
- Triple 3000W 80 PLUS Titanium redundant power supply

Applications

High-Performance Computing Server, High Converged Server, Servers for Hybrid/Private Cloud...

Specification

Dimensions	3U 4-Node (W447 x H130.8 x D895 mm)	RAID	Require RAID add-in cards Onboard VROC key header
Motherboard	MA84-HD0	PCIe Expansion Slots	16 x LP PCIe Gen5 x16
CPU	Intel® Xeon® 6 Processors - Intel® Xeon® 6900-Series Processors Dual processor per node, TDP up to 500W	I/O Ports	Top: 8 x USB 3.2 Gen1, 4 x Mini-DP, 8 x RJ45, 4 x MLAN
OS Compatibility	OS Support List	Backplane Board	PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s
Socket	8 x LGA 7529 (Socket BR)	TPM	4 x TPM headers (SPI), Optional TPM2.0 kit: CTM012 4 x PRoT connectors (only enabled on RoT SKU)
Chipset	System on Chip	Power Supply	Triple 3000W 80 PLUS Titanium redundant power supply AC Input: 100-240V *The system power supply requires C19 power cord.
Memory	12-Channel DDR5 RDIMM/MRDIMM, 96 x DIMMs [RDIMM] Up to 6400 MT/s [MRDIMM] Up to 8800 MT/s ^[1] ^[1] MRDIMMs are only supported with Intel® Xeon® 6 Processors with P-cores.	System Management	ASPEED® AST2600 Baseboard Management Controller ASPEED® AST2620 Chassis Management Controller GIGABYTE Management Console web interface
LAN	8 x 1Gb/s LAN (4 x Intel® I350-AM2), Support NCSI 4 x 10/100/1000 Mbps Management LAN	Operating Properties	Operating coolant temperature: 20°C to 35°C Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Video	Integrated in ASPEED® AST2600 x 4 - 4 x Mini-DP	Packaging Content	1 x H374-A81-IAW1 8 x CPU heatsinks 1 x Mini-DP to D-Sub cable 8 x Carriers
Storage	Bottom: 8 x 2.5" Gen5 NVMe/SATA/SAS-4 ^[1] ^[1] Storage card is required to support SATA and SAS drives.	Ordering Part Numbers	6NH374A81DR000IAW1*

