


# IoT SuperServer ARS-E103-JONX-L2

Compact fanless edge AI platform, with 6-core Jetson Orin™ NX module. Up to 117 TOPS.



## Key Applications

Artificial Intelligence (AI), Imaging and Computer Vision, Industrial Automation, Retail, Smart Medical Expert Systems, Healthcare, Digital Signage Kiosk, Interactive info system,

## Key Features

- Fanless DIN Rail Mounted System Jetson Orin NX Fanless Edge AI Inferencing System;
- 6-core Arm® Cortex® -A78AE v8.2 64-bit CPU 1.5MB L2 + 4MB L3 (2 GHz max);
- Up to 8GB LPDDR5X onboard memory;
- 1024-core NVIDIA Ampere GPU with 32 Tensor Cores, Up to 117 TOPS;
- 1 10G/1G LAN optional by Sku (10G: -H(2), 1G: -L(2)) 4 1Gbe w/ POE or 2 x1Gbe w/ PoE+ (by AOM-POE-001 jumper setting);
- 1 M.2 B-key 3042/3052 (USB3.2, USB2.0) w/ dual nano-SIM 1 M.2 E-key 2230 (PCIe x1, USB2.0) 1 M.2 M-key 2280 (PCIe4.0 x4);
- 1 NVMe 2280 at M.2 M-Key;
- DC 9-36V Operating Temperature -25 to 60 (-13°F to 140°F) with 0.7m/s airflow and Industrial Grade peripherals;



<b>Form Factor</b>	Fanless Embedded Enclosure: 185 x 80 x 140mm (7.28" x 3.15" x 5.5") Package: 290 x 200 x 230mm (11.42" x 7.87" x 9.06")
<b>Processor</b>	Arm® Cortex®-A78AE v8.2 64-bit CPU 6C/6T; 4MB Cache
<b>System Memory</b>	Slot Count: Onboard Memory Max Memory: 16GB ECC LPDDR5X
<b>Drive Bays Configuration</b>	1 M.2 PCIe 4.0 x4 NVMe slot (M-key 2280(default))
<b>Expansion Slots</b>	1 M.2 PCIe 4.0 x1 slot (E-key 2230(default); USB 2.0) 1 M.2 slot (B-key 3052(default)/3042; USB 3.0)
<b>On-Board Devices</b>	Chipset: System on Chip Network Connectivity: 4 RJ45 1GbE with Intel® I210-IT 1 RJ45 1GbE with SoC No NIC option supported
<b>Input / Output</b>	LAN: 4 RJ45 1 GbE LAN ports (Intel® I210-IT) 1 RJ45 1 GbE LAN port (SoC) USB: 1 USB 3.2 Gen2 Type-C port(Front) 3 USB 3.2 Gen2 Type-A ports(Front) Video: 1 HDMI 2 port(Front) Serial: 2 COM RS232/RS422/RS485 ports(Front) Others: 1 CANBus port 1 4 DI/4 x DO (terminal block) port

